



GENERAL NOTES:

1. MANHOLE RING AND COVERS CANNOT BE COVERED, OR OBSCURED BY LANDSCAPING, PAVEMENT, ETC.
2. INLET AND OUTLET PIPES SHOULD BE SCHEDULE 40 PVC, AND CANNOT BE COVERED OR CAPPED.
3. INLET PIPE MUST BE A MINIMUM OF 4" IN DIAMETER. VERTICAL PIPE ON OUTLET SIDE MUST BE A MINIMUM OF 6" IN DIAMETER.
4. SEPARATOR SHOULD NOT BE LOCATED IN AN ENTRANCE, EXIT, DRIVE-THRU, OR UNDER A MENU BOARD. IF SEPARATOR IS LOCATED IN A DRIVE/PARKING AREA, IT MUST CONTAIN TRAFFIC RATED RINGS AND COVERS AND MEET H-20 LOADING.
5. MINIMUM SIZE : 1000 GALLONS

REVISED	F.B.	PG.	DATE: 7/29/02
			SCALE: NTS
			DRAWN BY: MHW
			CHECKED BY: DFD
			CITY ENGINEER: FAP

STANDARD DETAIL  
IN GROUND OIL/GRIT SEPARATOR

OFFICE OF THE  
CITY ENGINEER  
GASTONIA, N.C.

FILE NO. 71B-29