



SEE STANDARD DETAIL 71F-9

SEE STANDARD DETAIL 71F-9

BEVELED EDGE TENSION BANDS AT 15° O.C.

END, CORNER, AND PULL POST, 3" O.D. GALVANIZED ASTM SCHEDULE 40 PIPE

SINGLE LATCH, MALLEABLE IRON GRAVITY TYPE

3/8" TAKEUP ROD

No. 7 W & M GAGE ALUMINIZED SPRING COIL OR CRIMPED WIRE

2" O.D. GALVANIZED ASTM SCHEDULE 40 PIPE  
NOTE: REMAINDER OF GATE FRAME IS COMPOSED OF 1-5/8" O.D. GALVANIZED ASTM SCHEDULE 40 PIPE

HINGES, MALLEABLE IRON FORGINGS

**NOTES:**

- (1) TOP BARS AND HORIZONTAL BRACES ARE 1-5/8" O.D. GALVANIZED ASTM SCHEDULE 40 PIPE.
- (2) ALL FABRIC SHALL BE No. 11 W & M GAGE WITH 1-3/4" MESH.
- (3) ALL GATE FRAMES SHALL HAVE WELDED JOINTS.

REVISED	F.B.	PG.	DATE: 2-8-79
12/20/79			SCALE: NTS
			DRAWN BY: D.D.S.
			CHECKED BY: FRW, FAP
			CITY ENGINEER: FRW

## STANDARD DETAIL

### TENNIS COURT GATE DETAIL

OFFICE OF THE  
CITY ENGINEER  
GASTONIA, N.C.

FILE NO. **71F-10**